

REGULAR CONFIGURATION

MODEL	JC35TA	JC35TS-RS2	JC35TS-RS3	JC35TS-D43	JC35TS-D6	JC35TH3	JC35TT-RS3	JC35TT-D43
PIC								
Lift Column Model	EF	RS2	RS3	D43	D6	/	RS3	D43
Motors	1	2	2	2	2	1	3	3
Segments	2	2	3	3	3	3	3	3
Leg Dimension(mm)	100*75 Rectangle	80*50 Rectangle	80*50 Rectangle	70*70 Square	Cycle 280mm Hexagon	75*75 Square	80*50 Rectangle	70*70 Square
Foot Dimension(mm) (Option)	/	Flat 700*70 Flat 600*70 TB 670*70	Flat 700*70 Flat 600*70 TB 670*70	Flat 700*80	Arch 680*70	Flat 700*80	Flat 700*70 Flat 600*70 TB 670*70	Flat 700*70 Flat 600*70 TB 670*70
Loading Capacity(N)	800	1000	1000	1000	1000	900	1500	1500
Speed(mm/s)	20	20	35	35	35	20	35	35
Lowest Position(mm)	650	716	623	623	610	560	623	623
Highest Position(mm)	1100	1210	1268	1253	1290	1190	1268	1253
maximum width(mm)	1000	1600					1600x1600	
Minimum width(mm)	/	1060					1060x1060	
Side Board Width(mm)	700	575					575x575	
Recommended Top Panel	1000x700	Length 1400-1800mm , Width 600-1000mm					/	
Running Power(W)		<300					<400	
Standby Power(W)	<0.2							
Overload Protection	Internal							
Color	Black Grey Pink	9005 Black , 7045 Grey, 9016 White						
Standard	CE , UL							

Jiechang has setup a Global distribution network,
providing their customers with regional support worldwide



EN527-1

EN527-2

EN527-3

ISO9001:2008

ISO14001:2004

ISO21016



ZHEJIANG JIECANG LINEAR MOTION TECHNOLOGY CO.,LTD

Address: Provincial High Tech Park, Xinchang, Zhejiang ,China
Post code: 312500
Tel: +86-575-86297980
Fax: +86-575-86297960
Web: www.jiechang.com
E-mail: Sales@jiechang.com



PRODUCT CATALOG
HEIGHT ADJUSTABLE TABLES



www. jiechang.com



Lift Column & Controller

Lifting columns are the ideal drive elements and perfect choice for a wide range height adjustable tables.

The whole technology is integrated and not visible from the outside. These lifting columns do not need any additional coverings,they can be combined and synchronised.

Some columns are very sturdy and crossbar is not necessary

RS2  Load Capacity(N) Speed up to (mms) Input(VDC) Stroke Length(mm) Retracted Length(mm) Color Limit Switch Standard 800 20 24 500 650 Black, Grey, White No limited switch CE UL	RS3  Load Capacity(N) Speed up to (mms) Input(VDC) Stroke Length(mm) Retracted Length(mm) Color Limit Switch Standard 800 35 24 650 560 Black, Grey, White No limited switch CE UL	D43  Load Capacity(N) Speed up to (mms) Input(VDC) Stroke Length(mm) Retracted Length(mm) Color Limit Switch Standard 800 35 24 630 560 Black, Grey, White No limited switch CE UL	D5  Load Capacity(N) Speed up to (mms) Input(VDC) Stroke Length(mm) Retracted Length(mm) Color Limit Switch Standard 800 35 24 660 535 Black, Grey, White No limited switch CE UL	D6  Load Capacity(N) Speed up to (mms) Input(VDC) Stroke Length(mm) Retracted Length(mm) Color Limit Switch Standard 800 35 24 680 530 Black, Grey, White No limited switch CE UL	JCB35N  Can Connect 4 Columns Max Output Voltage(VDC) 31 Input Voltage (VAC) :110/230 Transformer Power : 200/360 Standard: :CE / UL	JCB35N1  Can Connect 2 Columns Max Output Voltage(VDC) 29 Input Voltage (VAC) :110/230 Transformer Power : 200 Standard: :CE / UL	JCHT35M1A  Touch Screen With Blue Backlight LCD Display Current Position Color: White Connect JCB35N Control Box	JCHT35M1B  Touch Screen With Blue Backlight LCD Display Current Position Color: White Connect JCB35N Control Box

Height Adjustable Table

Are you facing more and more psychological subhealthy issues like Back&Neck Pain ,Eye Strain, Carpal Tunnel Syndrome et.? This is because we are spending more and more time sitting at the desks.

Height adjustable desk offers a perfect solution that easily change your work space from sitting to standing with just push on one button.