

## B15-2



### SUCTION CUP WITH SHORT BELLOWS

- ▶ Suitable for level adjustment.
- ▶ Lifting movement to separate small and thin objects.
- ▶ Only lightweight objects should be handled when the lifting force is parallel to the surface.

### LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm <sup>3</sup>	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
2.9	5.9	8.9	—	—	—	1.1	5.0	6.5	1.5

### MATERIAL SPECIFICATIONS


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	60	-40–110
Silicone, SIL	Red	50	-40–200

### MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

## ORDERING INFORMATION

Complete suction cups	Art. No.
Suction cup B15-2 Chloroprene, M5 male	3250037
Suction cup B15-2 Silicone, M5 male	3250037S



Rubber parts	Art. No.
Suction cup B15-2 Chloroprene	3150230
Suction cup B15-2 Silicone	3150230S



Fittings	Art. No.
Fitting M5 male, 10-15	3107030

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.