

BL40-2



SUCTION CUP WITH LONG BELLOWS

- ▶ Suitable for level adjustment.
- ▶ Lifting movement to separate small and thin objects.
- ▶ Less suitable when the lifting force is parallel to the surface of the object.

LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
1.1/11.0*	2.2/22.0*	—	—	—	—	27	11	33	10

*Lifting force with reinforcement rings.

MATERIAL SPECIFICATIONS


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	60	-40-110
Silicone, SIL	Red	50	-40-200

MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

ORDERING INFORMATION

	Complete suction cups	Art. No.
A	Suction cup BL40-2 Chloroprene, 1/8" NPSF female, with mesh filter	0101527
B	Suction cup BL40-2 Chloroprene, G1/4" male, with mesh filter	0101522
B	Suction cup BL40-2 Chloroprene, G1/4" male, with mesh filter and dual flow control valve	0101529
C	Suction cup BL40-2 Chloroprene, G3/8" male, with mesh filter	0101524
D	Suction cup BL40-2 Chloroprene, 5x1/8" NPSF female	0101526
D	Suction cup BL40-2 Chloroprene, 5x1/8" NPSF female, with dual flow control valve	0101533
A	Suction cup BL40-2 Silicone, 1/8" NPSF female, with mesh filter	0101540
B	Suction cup BL40-2 Silicone, G1/4" male, with mesh filter	0101535
B	Suction cup BL40-2 Silicone, G1/4" male, with mesh filter and dual flow control valve	0101542
C	Suction cup BL40-2 Silicone, G3/8" male, with mesh filter	0101537
D	Suction cup BL40-2 Silicone, 5x1/8" NPSF female	0101539
E	Suction cup BL40-2 Chloroprene, 1/8" NPSF female, PA	0110946
E	Suction cup BL40-2 Silicone, 1/8" NPSF female, PA	0110341



Rubber parts	Art. No.
Suction cup BL40-2 Chloroprene	0101119
Suction cup BL40-2 Silicone	0101120



Fittings	Art. No
Fitting 1/8" NPSF female, 30–40, with mesh filter	0101153
Fitting 1/8" NPSF female, 30–40, with dual flow control valve	3251006
Fitting G1/4" male, 30–40, with mesh filter	3250091
Fitting G1/4" male, 30–40, with mesh filter and dual flow control valve	3251007
Fitting G3/8" male, 30–40, with mesh filter	3250086
Fitting G3/8" male, 30–40, with mesh and dual flow control valve	3251009
Fitting 5x1/8" NPSF female, 30–40	0100261
Fitting 5x1/8" NPSF female, 30–40, with dual flow control valve	3251011
Fitting 1/8" NPSF female, 30–40, PA	3150197

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.

Spare Part	Material	Temperature range °C	Art. No.
Reinforcement ring for BL40-2 & B-BL40-2, 4x	Polyamide, PA	-40–110	3150073