

F15MF



FLAT SUCTION CUP WITH CLEATS, MARK FREE

- ▶ Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- ▶ Suitable for flat surfaces.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.

LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
4.0	8.0	12.0	4.5	9.0	14.5	0.37	17	1.0	0.8

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Thermoelastic polyurethane, TPU	Transparent white	81	-20–80

MATERIAL RESISTANCE


Wear resistance	Oil	Weather & Ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Excellent	Excellent	Excellent	Poor	Poor	Poor	Good	Good

SUCTION CUPS F-MF




ORDERING INFORMATION

Complete suction cups	Art. No.
Suction cup F15MF Thermoelastic polyurethane, M5 male	3250074



Rubber parts	Art. No.
Suction cup F15MF Thermoelastic polyurethane	3150269



Fittings	Art. No.
Fitting M5 male, 10-15	3107030

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.

Suction cups
F-MF